

ДЭС VOLVO 167-278 кВА

Technical Specifications



ENGINE

- VOLVO series heavy duty diesel engine
- 4 cycle, water cooled, turbocharged & air to air charge cooled / turbocharged & air to water charge cooled
- Direct injection
- Electronic governor system
- 24 volt self-starter and charger alternator
- Changeable air, fuel and oil filter
- Tropical type radiator
- Flexible fuel pipe
- Oil discharge valve and extension pipe
- Industrial type silencer, exhaust spiral or compensator
- Maintenance free battery
- Engine block water heater (in automatic models)
- Diesel gen-set maintenance and operating instructions and electrical circuit diagram

QUALITY STANDARD

Our generators are manufactured in compliance with VDE 0530, BSE 4999 BS5000, IEC 34, TS ISO 8528, TS EN ISO 3744, TS EN ISO 3746, TS EN 60034-1, TS EN 60204-1, TS EN 60335-1, TS EN 61439-1, EN 61000, TS EN ISO12100 standards.

We have ISO 9001:2008, ISO 14001:2004, OHSAS 18001:2007 and ISO10002:2006 management system certificates from Kiwa & MEYER, an accredited independent quality organization.

Our generators up to 400 kw are manufactured in compliance with 2000/14/EC European noise emission directive and certified from Ente Certificazione Macchine.

We also have TS ISO 8528-4, TS ISO 8528-5, TS EN 13501-1+A1:2013 flame retardancy and TS EN ISO 9227 certificates against anti-corrosion together with CE Declaration.

ALTERNATOR

- Brushless, single bearing, flexible disc 4 poles alternator for harmonic failure
- H type isolation class
- IP 21-23 protection class
- Self exciter
- Electronic automatic voltage regulator
- Stator 2/3 step for harmonic failure

- The alternator windings are protected by insulating varnish against oil and acid.

EXTRA EQUIPMENTS

- Charge ammeter
- Moulded case circuit breaker (in automatic models)
- Hospital/Critical type silencer
- Sound-proof canopy
- Mobile - trailer
- Synchronization control panel for 2-16 gensets
- 3 pole/4 pole automatic transfer panel (A.T.S.)
- Fuel and oil heater
- Alternator heater
- Automatic fuel filling system
- Fuel-water separator filter
- PMG warning system

CANOPY

- Modular type sound-proof canopy
- Canopy installation executed with screw and nut, without welding process
- Epoxy and polyester powder painted canopy
- Canopy designed for easy maintenance
- Lockable doors on both sides of canopy
- Emergency stop button
- Transparent panel inspection window

AUTOMATIC CONTROL PANEL

- LCD display screen
- Battery charger
- Hardware and materials needed
- USB port & RS-485 output

GEN-SET SAFETY PROTECTION & ALARMS

- High water temperature
- Low oil pressure
- High & low engine speed
- Low radiator water level
- Over current load
- High & low genset voltage
- Start/stop failure



Easy maintenance canopy design



Refilling from the outside of the canopy



Canopy made of galvanized steel



Warning system for decreasing fuel with electronic fuel level sender



VOLVO Series Diesel Generator Sets 167-278 kVA

MODEL				E VL XX 0167	E VL XX 0205	E VL XX 0224	E VL XX 0278
GROUP	GEN - SET POWER	STAND BY	kVA	167	205	224	278
			kW	133	165	179	219
		PRIME	kVA	152	186	201	250
			kW	121	149	161	200
	CANOPY DIMENSION (W x L x H) mm			1150 x 3820 x 2460	1150 x 3820 x 2460	1150 x 3820 x 2460	1150 x 3820 x 2460
	CANOPY WEIGHT kg			1870	2165	2165	2330
	OPEN DIMENSION (W x L x H) mm			1150 x 2700 x 1660	1150 x 2700 x 1860	1150 x 2700 x 1860	1150 x 2700 x 1920
	OPEN WEIGHT kg			1570	1865	1865	2030
ENGINE	BRAND			VOLVO	VOLVO	VOLVO	VOLVO
	TYPE			TAD 731 GE	TAD 732 GE	TAD 733 GE	TAD 734 GE
	POWER	STAND BY	kW	148	179	195	238
		PRIME	kW	133	160	175	213
	SPEED (rpm)			1500	1500	1500	1500
	CYCLE			4	4	4	4
	DISPLACEMENT (lt)			7,15	7,15	7,15	7,15
	NUMBER OF CYLINDERS			6 IN LINE	6 IN LINE	6 IN LINE	6 IN LINE
	BORE AND STROKE (mm x mm)			108 x 130	108 x 130	108 x 130	108 x 130
	COMPRESSION RATIO			18 : 1	18 : 1	18,1 : 1	17 : 1
	GOVERNOR TYPE			ELECTRONIC			
	INDUCTION			TURBOCHARGED - AIR TO AIR			
	COMBUSTION SYSTEM			DIRECT INJECTION			
	COOLING SYSTEM			WATER			
	FUEL CONSUMPTION (lt/h)	100% OF PRIME POWER		34,04	40,57	45,00	51,73
		75% OF PRIME POWER		25,65	30,43	33,44	41,27
50% OF PRIME POWER		17,73	20,86	22,6	29,54		
TOTAL LUBRICATION SYSTEM CAPACITY (lt)			20	34	34	29	
TOTAL COOLANT CAPACITY (lt)			23,8	37	38	32	
FUEL TANK CAPACITY (lt)			585	585	585	585	

Emsa reserves the right to make changes in model, technical specifications, color, equipment & accessories without prior notice.