



## MJH

<b>Model</b>	MJH
<b>Power</b>	Up to 14.000 kVA
<b>Voltages</b>	Up to 15.000 V
<b>Frame</b>	400 ± 1.250
<b>Poles</b>	4, 6, 8, 10 and 12 (over contact MM)
<b>Cooling</b>	IC 01
<b>IP</b>	IP 23. Available up to IP 44 with filters.
<b>Enclosure</b>	ODP - Open Drip Proof
<b>Main Applications</b>	Data center, Emergency, PRP and COP, Stand-by, UPS
<b>Sector</b>	Power generation

Poles	<b>4 Poles</b>	<b>6 Poles</b>	<b>8 Poles</b>	<b>10 Poles</b>	<b>12 Poles</b>
kVA   60 Hz	10.000	12.500	12.500	12.500	10.000

Certificates and testing	
<b>Applicable standards</b>	<p>Generators are designed in compliance with:</p> <p>IEC EN 60034 - 1            BS 4999 - 5000            VDE 0530            NF 51 - 100            NF 51 - 111            OVE M - 10            NEMA MG 1.32</p> <p>Generators conform to EU rules.            UL/CSA certifications available on request.            Adherence to ISO 8528 group G performance classes.</p>
<b>Certificate</b>	<p>Test Certificate supplied with the machine.            Material certificates in accordance with EN 10204 : 2001 can be supplied.</p>
Main components	
<b>Housing</b>	<p>Rigid frame, rugged welded steel fabrication (EN 10025 - S235 JR).            Frame is provided with side ribs to increase the strength.            Marelli Generators for continuous duty operation are designed to meet vibration levels per IEC 60034-14, ISO 10816-1 and BS 5000-3.</p>
<b>Shield</b>	<p>Made of spheroidal graphite cast-iron (EN 1563) or grey cast-iron (EN 1561) up to 630 frame size.            Made of structural steel (EN 10025 – S235 JR) above.</p>
<b>Shaft</b>	<p><b>General data</b>            Made in carbon steel and obtained by lamination (EN 10083 – 2 C40 – TN).            Shaft is obtained by forging from 290 mm diameter and above.            The shaft is tested to ensure defect-free performance.</p> <p><b>Shaft design</b>            Double bearing generator: cylindrical shaft with key.</p>
<b>Main terminal box</b>	<p>Mounted on top.            Made of formable steels EN 10130.</p>
<b>Fan</b>	<p>Made of aluminum alloy (EN 1706) or structural steel (EN 10025–S235 JR) depending on application requirements.</p>

Construction	
<b>Enclosure</b>	ODP - Open Drip Proof
<b>Cooling System</b>	IC 01 as per IEC60034-6
<b>Degree of protection</b>	IP 23 as per IEC60034-5
<b>Mounting</b>	Horizontal - IM 1001 or IM 1101 as per IEC 60034-7. Other mounting available on request.
Technical data	
<b>Stator/Rotor core</b>	Laminated and enamel-insulated on both sides to minimise eddy-current losses
<b>Rotor</b>	Salient pole type. Made by copper flat wire. H class insulated with enamel coating. Winding retaining by pass-through bars of high quality steel. Rotating rectifier: Graetz diode bridge with 6 diodes. Rotors are dynamically balanced with a half key applied to the shaft extension in accordance with IEC 60034-14 to vibration grade normal A. Special vibration level construction are available.

<b>Bearing</b>	<p><b>General data</b></p> <p>Single or double antifriction bearing grease lubricated (ball or roller type) or oil lubricated sleeve bearing.</p> <p>The theoretical lifetime of bearings, L10h according to ISO 281/1 standard, of standard horizontal construction generators, without external forces (radial and / or axial) is in excess of 50.000 hours. On request, the lifetime of bearings, L10h can be in excess of 100.000 hours. Locating bearings are on the D end side and floating bearings on the ND end side.</p> <p><b>Bearing selection</b></p> <p>Antifriction bearings up to 800 frame size included.</p> <p>Sleeve bearings from 900 frame size included (available for smaller frame sizes).</p> <p><b>Regreasing system:</b></p> <p>Up to 400 frame size:</p> <p>D-end bearing is fitted with inner bearing cap and with gerase nipple</p> <p>ND-end bearing is prelubricated with inner bearing cap and without grease nipple</p> <p>450 frame size and above: both bearings are fitted with grease nipple.</p> <p><b>Bearing insulation</b></p> <p>ND end bearing can be insulated to prevent any harmful circulating current from passing through the bearing surfaces.</p> <p>Insulated antifriction bearings in standard configuration:</p> <p>4, 6 poles: insulated ND end bearing from 630 frame size</p> <p>8 poles: insulated bearing from 400 frame size</p> <p>10 poles: insulated bearing from 500 frame size</p> <p>All ND end sleeve bearings are insulated as standard.</p>
<b>Impregnation system</b>	<p>Stator and rotor are VPI treated with an unsaturated polyester amide resin which is polymerised in an oven.</p>
<b>Insulation system</b>	<p>Stator: F class insulated with a synthetic enamel (class H option with BH technology).</p> <p>Rotor: H class insulated with a synthetic enamel.</p>
<b>Protective treatments</b>	<p>Epoxivinilic and polyacrylic. Total minimum thickness 120 micromillimeters.</p> <p>Epoxivinilic: Epoxy two component products, with vinyl change.</p> <p>Polyacrylic: Two components polyurethane product formulated with unmodified hydroxyl acrylic resin.</p>

Operating conditions	
<b>Overloads</b>	<p>During continuous duty (S1), the following overloads are allowed:</p> <ul style="list-style-type: none"> <li>10% for 1 hour</li> <li>15% for 10 minutes</li> <li>30% for 4 minutes</li> <li>50% for 2 minutes</li> </ul> <p>These overloads must be occasional and followed by one hour of running at normal load or less.</p>
<b>Parallel operations</b>	<p>All generators are provided with a amply sized damper cage and are suitable for parallel operations with other generators, when equipped with the paralleling unit. A power factor regulator (to work in parallel with the main) is available on request.</p>
<b>Transient ratings</b>	<p>All generators can be designed to meet specific reactance values (<math>x'd</math> and <math>x''d</math>). Values can be confirmed by contacting Marelli Motori.</p>
<b>Three phase short circuit current</b>	<p>All generators equipped with overboosting device ensure a three phase short circuit current (<math>I_{cc}</math>) higher than 3 times the rated current (<math>I_n</math>): <math>I_{cc} &gt; 300\% I_n</math></p>
<b>Radio interference</b>	<p>All generators are equipped with Class B Group 1 radio interference filters as defined by EN 55011.</p>
<b>THD (Total Harmonic Distortion)</b>	<p>The no-load voltage wave form is sinusoidal with THD content less than 2%.</p>
<b>Vibrations</b>	<p>Vibration level is in accordance with ISO 10816. Measurement, evaluation and limits of vibration severity are in accordance with IEC 60034-14.</p>

**Auxiliary device**
**AVR**

Automatic voltage regulator mounted on board.

Size	Type
400 - 450	MEC 20 analog/ digital
500 - 560	M40FA610A analog
630 - 710	M63FA310A analog
800 - 1250	MEC 100 digital

Digital AVR available for all sizes on request.

**Overboosting device**

	Size	Type
Medium Voltage	All	CT + Overboosting device
High voltage	All	PMG

**Space heaters**

Heaters installed at ND-end side.

Size	Power(W)
400 - 560	400
630 - 710	600
800 - 900	800
1000	1000
1120	1200
1250	1400

**RTD-PT100**

RTD devices in standard configuration:

1+1 RTD on each phase of stator winding

1 RTD on each bearing

Terminals in auxiliary terminal box.

Other configurations available:

DUPLEX type

RTD for inlet / outlet air

## Optional features

### List

Reinforced construction for high linear vibrations  
flanged shaft for direct coupling with engine flywheel (in case of single bearing solution)  
neutral point terminals in separate terminal box  
increase protection degree up to IP 44 with filters  
lifted feet to couple the generator with engine on existing baseframe  
redundant rotating rectifier with 12 diodes  
insulated bearing and earthing brush  
AVR supplied loose  
automatic power factor control (analog type)  
digital AVR MEC100 for frame 400 – 710 (supplied loose)  
digital AVR MEC100D with diode failure monitoring  
redundant AVR system  
excitation/overboosting PMG mounted on generator  
lubrication system for sleeve bearing  
other options available on request.